Residential units Commercial spaces Stairways Parking: basements -1 and -2 Commercial spaces Floor 0 Premium apartments Floor 5-6 Penthouses Floor 5-6 Gross floor area above ground 11,400 m2 Gross floor area below ground 5,580 m2

Construction typology

Reinforced concrete structure, diaphragm walls, pillars and solid slabs

Characteristics

GENERAL

Reinforced concrete foundation slab Concrete type: HA-25-B-30-IIa + Qb Steel type: B-500-S / B-500-T Concrete screen walls 45 cm, depth 16 m. Double grilled, diameter 12cm

The structure is comprised of concrete pillars across all floors except for the the central core which is supported by screens. Waffle slabs and concrete slabs are the horizontal structural elements.

Concrete type: HA-30-B-20-IIIa Steel type: B-500-S (corrugated bars), B-500-T

Three types of interior finishes: Raw, Vanity & Island

CEILIGHT HEIGHTS Ground floor 3,00 m Floors 1-6 2,60 m

PERMISSIBLE LOADS Residential zones 5'00 Kn/m2 Stairways 3'00 Kn/m2 Terraces and balconies 2,50 Kn/m2

COMMUNAL AREAS

Pool and solarium Large concrete style pool (83m2) with decking and lounge area. Ceramic tiles 30x60cm Mistery grey Gresite Bisazza Flow Ref. SL 9 Pool depth 1.10m. Surface 60m2 Toilet, shower and changing room

High-tech gym Exposed concrete walls Heavy duty interlocking gym flooring High-tech gym equipment - Tecnogym Gym surface: 60m2

XO wellness Sauna:

3 leveled sauna. Wall boards, beechwood and elements. 220x250x226.5cm Interior finishes: **HEMLOCK Softline** Micro terrazzo flooring

Profi Klafs Steam room 220x220x225cm Enamelled ceramic tiles

Natural stone tiles

XO Lounge Indoor/outdoor lounge space with on-site cafe. Organic moss wall Flooring: Ceramic tiles GUBI cloud -Living ceramics

Product

OVERVIEW

Representative residential commercial and building. High- end properties

The apartments are organised in different typologies of one, two, three and four bedrooms, and integrate generous and very bright living areas with fine quality finishes. Large private terraces, gardens and rooftops. The six floor layouts surround a central core where the ground floor is freed to a private access garden

Facades displaying distinctive and varied volumetric compo- sitions. The differing building's patterning of each facade is generated by as- sembling the balcony units and el- ements in varying secuences, while mantaining a cohesive design language throughout, show- casing unique textures

Basement screens - galvanized steel sheets, galvanized steel profile structure. Phosphate paint coating.

COMMUNAL AREAS

Stainless steel perimeter fence with interior safety glass (smoked). Thickness: 10 cm Flooring: Ceramic tiles GUBI cloud -Living ceramics Garden seating area and concrete firepit LED lighting

Exposed concrete walls Reception bar Post boxes Intercom system Electric swinging door Surface: 45m2

Hallways Concrete syle finish Flooring: Ceramic tiles GUBI cloud -Living ceramics LED sensored lighting

Parking Basements -1 and -2 On-site access Controlled garage parking with 114 parking spots Electric vehicle charging station for every spot

High-tech security system & porter 24 hour porter ans security service (24-hour CCTV) coverage to communal areas.

Appearance

FACADES

Exposed reinforced concrete style facade

Solar shading

Low-emissivity glass, roller blinds

Joinery
Minimalist anodized aluminum joinery

Enclosings
The building's enclosings are resolved using glazing systems 14cm honeycomb brick walls and double layered plasterboard chamber with thermal insulation. Facade's exterior cladding is panelled with thermo-insulated Equitone fiber cement and an aluminum

Terraces and balconies are waterproofed with a bitumen based membrane and

Access door - Standard armored apartment access door with step light 85.6x 203cm. Composed of: electrogalvanized steel sheet reinforced by omega profiles. Finished with a smooth board on both sides. Paintcoated in polyester powder; security lock with three frontal closing points (10 latches) with security bulb, rubber seal, and automatic closure to the ground.

Interior doors

47mm 1 leaf passage frameless door -Inverse portaro. Made of wood and MDF boards. Hinged frame made of solid single-walled wood with a EPDM perimeter joint. Perfectly edged with a matt white RAL 9010 lacquered finish. Concealed stainless steel hinges recessed in the swinging frame. Simonswerk Tectus 340 3D F2, Tesa 136 lock, Inox Glutz Mod. 5056 handle.

WINDOWS AND BLINDS

4 joinery types 1. TECHNAL UNICITY window and balcony: Hinged window in extruded aluminum alloy AW-6063/AW-6060. Anodizable quality according to EN UNE 38-337 and T5 tempering. Frame and blade of 85mm depth.

2. Sliding window LUMEAL GA by TECHNAL Guillotine HYLINE large format 3. Aluminum window, guillotine type with 1 moving leaf. Hyline model. low-e tempered and colorless solar glass.

4. Large format Hyline 40 sliding window. Aluminum door with 1 sliding leaf (one rail), dimensions 2500x6000mm. Low e-tempered and colorless solar glass, warm-edged with argon gas.

All carpentry elements are complete and include crystals, galvanized steel subframes and/or auxiliary tubes for support and assembly. Fittings in the same color as profiles, guides, drainage channels AISI 304 stainless steel. Integrated flooring, "air-inlateral" aerators'

Solomatic Blinds - 80 System Profil; adjustable shutter. Self-supporting motorized exterior blind system for direct mounting to the window frame. Collection cords (grey) with edge protection and UV protection. Thermo-lacquered extruded aluminum skirting and guide rails (77 x 27 mm). Weatherproof/soundproofing system.

INTERIOR FINISHES

Impact-proof laminate placed underneath the flooring. Fonoless 8008 PP 3 different types

Floating floor with radiant heat on noise reduction mat. Ceramic tiles GUBI cloud 120x120cm

Floating floor with radiant heat on noise reduction mat. Herringbone oak wood parquet, (3 colour choices)

Floating floor with radiant heat on noise reduction mat. Ceramic tiles GUBI light 120x120cm

Interior partitions - Walls 14 cm perforated ceramic brick wall, laminated on both sides, formed by a 70mm structure of wide galvanized steel sheet profiles. Partition formed by two 15mm thick PLADUR® plates, N type, water-repellent in humid areas. Level 1 (Q1) cladding. Matt plastic painting finished walls. Drop ceilings

Special features - Art wall Raw: Exposed concrete style walls Vanity: In-built large picture frame Island: Organic moss wall

Baseboards Orac - DX163-2300 square Shadowgap

Electric installation Electric blinds Plugs/USB ports Light switches - Gira E2 Doorbell system

BUILDING SYSTEMS

Air conditioning

Air conditioning system by ducts. 2-tube fan coils with EC Inverter pressure engine, with temperature control in each room - Daikin

Underfloor heating Schlüter®-Bekotec-Therm-EN / PF system across all rooms. Quick set-up, uniform heat distribution, low operating temperature and saving energy consumption. Temperature control in all

Consumption costs are distributed according to individual spending.

Building technology - Home automation Integrated KNX system for domestic automation including lighting, temperature and heating control through an In-built home screen. Iconic - Gira G1

Ventilation

Double-flow controlled mechanical ventilation with heat recovery system (over 85%) - Silber

Illumination

Energy efficient LED lighting

Access control Alarm, CCTV CCTV system across communal areas, monitored through the residential access gate. Pre-installation of home sound system. Fire detection and warning system (mobile messaging) in the kitchen area.

Aspe Trivium Flex Adapt+ electric elevator (no machine room). Capacity: 11 people, 900 Kg. Cab: 1400x 1400mm. 6 stops and 9 accesses with double boarding. LED lighting. **BATHROOMS**

Bathroom walls 3 different finishes

Flooring: Gubi light 120x120cm -Living ceramics Wall: White porcelain tiling 30x90cm Gubi cloud - Living ceramics. Star Azahar 30x90cm - Pavimarsa

Flooring: Gubi light 120x120cm -Living ceramics
Wall: Black and white porcelain tiling 5x30cm - Complemento

Island

Flooring: Gubi light 120x120cm -Living ceramics Wall: White porcelain tiling Star Azahar 30x90cm - Pavimarsa

Mounted double sink-basin -Catalano New Zero 125x50cm (master hatherooms) Mounted sink basin -Catalano New Zero 75x50cm In-built framed led mirror 40x20cm

In-built bathtub mod. Cube 170x80cm In-built bathtub mod. Serena 150x70cm Free-standing bathtub mod. Trento 170x80cm (* where applicable)

Wall-hung satin white toilets 55x35cm -Newflash Catalano Duofix cistern - Geberit Showers Two-way thermostatic shower mixer. Headshower and handshower Via tortona #149 Finox - Gessi

Antrax IT towel radiator (* where applicable)

Texturized fixtures mod. Via tortona - Gessi #149 Finox (Raw and island) #299 Black XL (Vanity)

SPECIAL FEATURES

Alarm system Installed and integrated

Electric vehicles Pre-installed electric charging sta- tions for every parking space

Geothermal energy Installation photovoltaics solar panels for community

Rainwater collection system: Rainwater tanks (located at the basement) guaranteeing water efficiency for pools and irrigation.

Electric vehicle charging stations pre-installed for every spot

Cellar and storage Individual underground cellars for every apartment

Bicycle storage room

Communal rubish colection room

Individual style full-equipped kitchen.

Set up according to apartment layout

Appliances Fridge/ Freezer - KFN 37232 Miele Wine fridge - KWT 6321 Miele

KITCHENS

Induction hob w/integrated extractor - KMDA 7633 Miele Oven - Pureline H2840 Miele Dishwasher - G4380 SCVi Miele

3N1 filtered steaming hot water tap L3N1C -Insinkerator. Designed and manufactured in Italy. 2.5 litre tank capacity, push down safety lever with self-closing hot water handle that's easy to grip.

Kitchen islands 3 different finishes

Raw: Brushed Gris Balear stone Vanity: White Carrara marble Island: White snow Krion

Raw: Lacquered wood in dark grey colour Vanity: Lacquered wood in white colour Island: Lacquered wood in white colour



+34 (0)871 858 513 | +34 600 98 20 09 PALMA@XO-JAY.COM WWW.XO-JAY.COM

XOJAY SHOWROOM JOAN MARAGALL 17-G, 07006 PALMA DE MALLORCA

OPENING TIMES

Building specifications The XO Residences Palma